



**HEAD OFFICE**  
 17 Tappeol-gil Ungchon-myeon Ulju-gun Ulsan Korea  
 Tel.82-52-228-7500 Fax.82-52-268-5578  
**OVERSEAS DIRECT**  
 Tel.82-52-228-7563 Fax.82-52-228-7530  
**SEOUL OFFICE**  
 Tel.82-2-2635-1380 Fax.82-2-2635-1382

KUKIL INNTOT CO., LTD.

KUKIL INNTOT is a professional manufacturer of gasket, packing coupling with the latest technology not only for the plant but also the plant maintenance and emergency repair.

## NON-ASBESTOS GASKET

*Type ' KN 11 '*

### Product Reference :

K/# KN 11

### Description :

The main components are Synthetic fibers with Neoprene binder to form non-asbestos joint sheet gasket.


### Service :

Maximum recommended Temperature : 370°C  
 Maximum recommended Pressure : 100 kg<sub>f</sub>/cm<sup>2</sup>

### Applications

Water & Oil  
 mild acids and alkalis  
 Utility Services.

### Construction :



Synthetic fibers + Neoprene binder

### Gasket Design Data : Standard ASME Section VIII Div.1

Thickness	Gasket Factor " m "	Min. Design Sealing Stress " y "
1.5t, 2.0t	2.75	3,700 psi
3.0t	2	1,600 psi

### Availability :

Gasket Size : Max. 1500mm (Non-seam)  
 Max. 5000mm (seam)  
 Thickness : 1.5mm , 2.0mm , 3.0mm , etc.

### Remark :

- The specification of product is written by manufacturer, and it is changed frequently.
- The recommended flange surface finish for INNOSILD KN 11 gasket is from 125~500AARH