



KUKIL INNTOT CO., LTD.

HEAD OFFICE
17 Tappeol-gil Ungchon-myeon Ulju-gun Ulsan Korea
Tel.82-52-228-7500 Fax.82-52-268-5578
OVERSEAS DIRECT
Tel.82-52-228-7563 Fax.82-52-228-7530
SEOUL OFFICE
Tel.82-2-2635-1380 Fax.82-2-2635-1382

RUBBER SHEET GASKET

Type ' KR 3 '

KUKIL INNTOT is a professional manufacturer of gasket, packing coupling with the latest technology not only for the plant but also the plant maintenance and emergency repair.

Product Reference :

K/# KR 3

Description :

Neoprene Rubber Sheetting is a 70° shore hardness Commercial Quality Chloroprene (Neoprene) and StyreneButadiene blended material. As they are susceptible to cold-flow should generally be used on flanges.

KUKIL KR3 gasket are used for fine chemicals, petrochemical, pharmaceuticals, foodstuffs, etc.

Service :

Maximum recommended Temperature : -40 ~ 120°C

Maximum recommended Pressure : 10 Kg/cm²

Applications

Strong acids and strong alkalis etc.

Various corrosive fluids, organic solutions.

Fluid where no contamination is allowed.

Where electrical insulation is required.

Construction :



CR Rubber (Chloroprene Rubber(Neoprene®))

Gasket Design Data :

shore hardness	Gasket Factor " m "	Min. Design Sealing Stress " y "
Below 75A	0.5	0 psi
Higher 75A	1.0	200 psi

Availability :

Gasket Size : Max. Ø1200

Thickness : 1.5mm, 3.0mm, etc.

Remark :

- The specification of product is written by manufacturer, and it is changed frequently.