



KUKIL INNTOT CO., LTD.

HEAD OFFICE
17 Tappeol-gil Ungchon-myeon Ulju-gun Ulsan Korea
Tel.82-52-228-7500 Fax.82-52-268-5578
OVERSEAS DIRECT
Tel.82-52-228-7563 Fax.82-52-228-7530
SEOUL OFFICE
Tel.82-2-2635-1380 Fax.82-2-2635-1382

RUBBER SHEET GASKET

Type ' KR 4 '

KUKIL INNTOT is a professional manufacturer of gasket, packing coupling with the latest technology not only for the plant but also the plant maintenance and emergency repair.

Product Reference :

K/# KR 4

Description :

KR 4 is a copolymer of styrene and butadiene, the most commonly used synthetic rubber. It has similar advantages and temperature used for natural rubber, and has better abrasion resistance, aging resistance, electrical resistance, cold resistance, and dynamic properties than natural rubber.

Service :

Maximum recommended Temperature : -50 ~ 100 °C
Maximum recommended Pressure : 10 Kg/cm²

Applications

Water, Alcohol.
Organic Acids, Ketones.
Aldehydes, Brake oil, etc.

Construction :



SBR Rubber (Styrene Butadiene Rubber)

Gasket Design Data :

shore hardness	Gasket Factor " m "	Min. Design Sealing Stress " y "
Below 75A	0.5	0 psi
Higher 75A	1.0	200 psi

Availability :

Gasket Size : Max. Ø1200
Thickness : 1.5mm, 3.0mm, etc.

Remark :

- The specification of product is written by manufacturer, and it is changed frequently.